Superior vinyl

Durability

Freedom from wear

Heat/cold resistance

Highest consumer satisfaction





Features



The Victorian Patio Door Performance Series is manufactured using the most advanced vinyl available.

Our high-grade resin recipe is unmatched for strength and wear reduction. Offering beauty and performance, it will not rot, rust, pit, or blister over time. The multi-chambered, all-vinyl frame is durable and easy to install - and its maximized strength withstands high winds and offers superior air tightness.

The Victorian's newly redesigned panels further reduce energy costs with more visually pleasing seams.

Sunview Patio Doors are available with a wide range of quality upgrades including security devices, blinds, colours, and finishing options.

Our goal is to deliver the highest levels of buyer satisfaction in the market!

Standard Hardware

Elite handles come as the standard door hardware.

Available in white or black.



Optional Frame & Sash

- 1^{1/4}", 2", or 3^{3/8}" frame extensions
- 4½" sill plate
- Brick mold
- Sill extensions

Optional Sidelites and Transoms

Frame your patio door in outdoor light with a transom or sidelite. The frame is made of PVC, virtually maintenance-free and available in a wide selection of finishes and glass types.

Vinyl Frame

- 5^{7/8} mechanically fastened vinyl frame
- Components easily installed and replaceable
- 3 weather seals
- Anodized screen track/stainless steel roller track
- 8 degree sill slope for optimal drainage

Durable Sash

- Reinforced with steel to withstand high wind loads
- Double perimeter seal for superior air-tightness
- Doors are easily and completely reversible
- Adjustable tandem ball-bearing rollers
- 1" sealed units for optimal thermal performance

Glazing

Enhancing the outstanding thermal efficiency is the 1" high-performance glazing found in **Low-E** glass and **Super**

Spacer® technology.

Our dual-glazed package meets

2020 ENERGY STAR®

program guidelines for environmental protection and superior energy efficiency.



Hardware & Glass Options

Optional Hardware

Optional stylish and contemporary handle sets with either single or twin-point locking systems in black, white or satin nickel.

These unique handle sets can be configured with heavy duty multi-point keylocks.











Optional Internal Mini-Blinds

• Fingertip operation

Nickel

- No external cords
- No dusting
- Low-E glass
- Only available for $59^{1/2}$ x $79^{1/2}$ and $71^{1/2}$ x $79^{1/2}$ doors

Maximum visibility to complete privacy at the tip of a finger. The lever raises, lowers or tilts the blinds sealed between the insulated glass to ensure a smooth maintenance-free operation.

Optional Security Locks



Two Position Kick Locks mount on the bottom of the operating door. Used as secondary lock. Available in white, beige or brown.



Guardian Locks mount on the top of the operating door; security bolt locks into the frame.

Available in white, beige or brown.



Folding Security Bars mount on the fixed side of the door frame and swing down to stop the door from operating.



Optional Decorative Grills


Internal grills are available in a wide range of design styles with colours that include **Flat Grills** in two-tone, white, brass and pewter, **Georgian Grills** in two-tone and white, and **Pencil Grills** in white, brass and pewter.

Optional Exterior Colours


Sunview's patio doors boast a wide range of exterior colour options that feature a durable finish that is also UV stable.


Specifications


Dimensions Door/Panel Configurations and Finished Sizes (Exterior view)




OX-Slide left









XO-Slide Right

OXO-Slide R to L or OZO-Slide L to R

X00-Slide R or 00X Slide L

OXXO-Slide R and Slide L from Centre

2 Panels

581/2 W	Χ	791/2 H
591/2~W	Χ	79 _{1/2} H
591/2~W	Χ	81 _{1/2} H
591/2 W	Χ	951/2 H
701/2 W	Χ	79 _{1/2} H
$71_{1/2} \text{ W}$	Χ	79 _{1/2} H
711/2 W	Χ	81 _{1/2} H
$71_{1/2} \text{ W}$	Χ	95 _{1/2} H
951/2~W	Χ	79 _{1/2} H
951/2~W	Χ	81 _{1/2} H
951/2~W	Χ	95 _{1/2} H

3 Panels

88 _{3/4} W	Х	79½ H
88 _{3/4} W	Χ	81 _{1/2} H
$88_{3/\!4}~W$	Χ	$95 \scriptscriptstyle{1/2}\ H$
1063/4 W	Χ	79 _{1/2} H
106 _{3/4} W	Χ	81 _{1/2} H
106 _{3/4} W	Χ	95 _{1/2} H
1423/4 W	Χ	79 _{1/2} H
1423/4 W	Χ	81 _{1/2} H
$142_{3/4}\;W$	Χ	95 _{1/2} H

4 Panels

117 _{1/8} W	Χ	79 _{1/2} H
117 _{1/8} W	Χ	81 _{1/2} H
1171/8 W	Χ	95½ H
1411/8 W	Χ	79 _{1/2} H
141 _{1/8} W	Χ	81 _{1/2} H
141 _{1/8} W	Χ	95½ H
1891/8 W	Χ	79½ H
189 _{1/8} W	Χ	81 _{1/2} H
189 _{1/8} W	Χ	95½ H

Performance Victorian Patio Doors meet standards AAMA/WDMA/CSA 101/1.S.2/A440-11 and CSA A440S1-09

Configuration	Performance Class and Grade	Air Leakage	Water Penetration Resistance	Design Pressure
0X / X0	LC-PG55	A3-0.2 L/s-m²	400 Pa (8.4 psf)	±2640 Pa (±55 psf)
0X / X0	LC-PG35	A3-0.4 L/s-m²	400 Pa (8.4 psf)	±1680 Pa (±35 psf)
OXO	R-PG50	A3-0.3 L/s-m²	360 Pa (7.5 psf)	±2880 Pa (±60 psf)
OXO	LC-PG40	A3-0.3 L/s-m²	360 Pa (7.5 psf)	±1920 Pa (±40 psf)
OXXO	LC-PG35	A3-0.5 L/s-m ²	260 Pa (5.4 psf)	±1680 Pa (±35 psf)

Distributed by:









Our products meet the ENERGY STAR® program guidelines to help protect the environment through superior energy efficiency.